

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location System Location					
Address 1654	OHINDS		ocation	Talankana Nimakan	
City St	off of	HUZ State MAN	710 5500A Proj	Telephone Number	
2000					
Owner Ranchy Menton Pumping Date 10/26/15 Contractor					
Maintainer MEYER SEWER MPCA License No. 915 Telephone Number 651-459-016					
What was done to the system? Report Liquid Capacity in Gallons					
Tank(s) Pumped					
Sludge and scum measured.			1000		
Do tanks need to be pumped?					
Yes No (If no provide measurements below)			Total Gallons Pumped: 2000		
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspect					
				JA., 07 116	
			·	pulling the A. Th	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped					
Tank Length	in. X Tank Width	in. X Tank D	epth in. =	Tank Volume (cubic inches)	
Tank Radius	in. X Tank Radius	in. X 3.14	= Tank Volume (cub	ic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch					
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons					
Scum Level in. X Gallons Per Inch = Scum Volume Gallons					
Sludge Volume	+ Scum Volume	= Total Slu	dge and Scum Volume	Gallons	
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %					
				*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than	
Scum Layer	TE			12 inches from the bottom of the outlet	
Effluent		fror	k Depth measured n invert of outlet	baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid	
Sludge Layer		pip	pipe to bottom of tank capacity.		
MI			10/0/1/19		
000			10/000/1		