

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location

Address 10315 Dellwood R	Telephone Number
	MW ZIP 55082 Property ID No./GEO Code
Owner Jacob Kooman Pumping Date 10/12/15	
Contractor /	
Maintainer MEYER SEWER MPCA	License No. 915 Telephone Number 651-459-016.
What was done to the system?	Report Liquid Capacity in Gallons
(Cank(s) Pumped	Tank 1: /500 Sumped Tank 2: 1000 Pumped
Sludge and scum measured. Do tanks need to be pumped?	Tank 3: Pumped Tank 4: Pumped
Yes No (If no provide measurements below)	Total Gallons Pumped: 2500
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
· PECEIVED	
JAN 07 2016	
PIRICHEALTH	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X	Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. X Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = 1	Fotal Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Cap	pacity = Percent Sludge and Scum in Tank %
Scum Layer Effluent Sludge Layer	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.
Cianatural	Date 10/12/15 Reset Form