

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 7424 994h St. N	Telephone Number
City DE NWOOC State	eM W ZIP55/10 Property ID No./GEO Code
	ping Date 10/2/15
Contractor /	
Maintainer MEYER SEWER MPC	A License No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: 1250 Pumped Tank 2: Pumped
Sludge and scum measured. Do tanks need to be pumped?	Tank 3: Pumped Tank 4: Pumped
Yes No (If no provide measurements below)	Total Gallons Pumped: 1250
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection	
	RECEIVED
	JAN 07 2316
	PUBLIC HEALTH
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X	Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X	3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
	Sludge Volume Gallons
Scum Level in. X Gallons Per Inch =	Scum Volume Gallons
Sludge Volume + Scum Volume =	Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
	*Tanks must be pumped if either of the following conditions exist:
Scum Layer Scum Layer	1. The top of the sludge layer is less than 12 inches from the bottom of the outlet
Effluent	Tank Depth measured baffle; or
Linucia	from invert of outlet 2. Total sludge and scum volume is greate:
Sludge Layer	pipe to bottom of tank capacity.