

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location			
Address 8/65 26th St1)	S# // Telephone Number		
City Lake Flows	State MUJIP	56047 Pro	perty ID No./GEO Code
Owner John Brash	Pumping Date /		
	Contracto	or	
Maintainer MEYER SEWER	MPCA License No	915	Telephone Number 651-459-011
What was done to the system?		Repo	rt Liquid Capacity in Gallons
Tank(s) Pumped		Tank 1: 1500	Pumped Tank 2: Pumped
Sludge and scum measured.	1 1		Pumped Tank 4: Pumped
Do tanks need to be pumped? Tyes No (If no provide measurements bek	ow)	Total Gallons Pump	ned: 1500
Visual Inspection (note any problems with the s			
		7,012, 7,77	es not serve as a compliance inspection
			JAN 07 2016
			UBLIC HEALTH
			0.000 5 9 9
*Tank Measurem	ents-Use Only If	Tank(s) Were NOT	Pumped
Tank Length in. X Tank Width	in. 🗶 Tank Dept	h in. =	Tank Volume (cubic inches)
Tank Radius in. X Tank Radius	in. X 3.14 =	Tank Volume (cub	ic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch			
Sludge Level in. X Gallons Per Inch	= Sludge Volu	me Gallo	ns
Scum Level in. X Gallons Per Inch	 = Scum Volum	ne Gallo	ns
Sludge Volume + Scum Volume	= Total Sludge	and Scum Volume	Gallons
Total Sludge and Scum Volume / Liqu	id Capacity	= Percent :	5ludge and Scum in Tank%
Scum Layer			*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet
Effluent Sludge Layer	from ir	epth measured overt of outlet o bottom of tank	baffle; or 2. Total sludge and scum volume is great than 25 percent of the tank's liquid capacity.