

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location	
Address 1400 Norcrest Avel	Telephone Number
City St. Vluvator State MN	ZIP 550%2 Property ID No./GEO Code
Owner Brian Krafthefor Pumping Date 9/32/15	
Contractor	
Maintainer MEYER SEWER MPCA License	No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: /500 Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped?  Tyes No (If no provide measurements below)	Total Gallons Pumped: 1500
Visual Inspection (note any problems with the system):	NOTE: This does not serve as a compliance inspection.
	RECEIVED
AN <b>0 5</b> 7016	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. <b>X</b> Tank Width in. <b>X</b> Tank D	Depth in. = Tank Volume (cubic inches)
Tank Radius in. <b>X</b> Tank Radius in. <b>X</b> 3.14	= Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. X Gallons Per Inch = Sludge	/olume Gallons
Scum Level in. <b>X</b> Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Total Slu	udge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity	= Percent Sludge and Scum in Tank %
fro	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.