

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

1

System Location	
Address 9960 57th St 11	Telephone Number
City Lake Elmo State MNZIP 55042 Property ID No./GEO Code	
Owner Rick Egersolor Pumping Date 9/22/15	
Contractor	
Maintainer MEYER SEWER MPCA License No.	715 Telephone Number 651-459-0163
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped Tank	1: /500 Pumped Tank 2: Pumped
Sludge and scum measured. Do tanks need to be pumped?	3: Pumped Tank 4: Pumped
	I Gallons Pumped: 1500
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
RECEIVED	
	JAN 0 5 2016
PUBLIC HEALTH	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. X Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Total Sludge an	d Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
from inver	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.