

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006

Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 7703 Harkness Au	re S Telephone Number
City Cottage Grove	State MUZIP 55016 Property ID No./GEO Code
Owner Jeff Lindbom	Pumping Date 9/23/15
Contractor	
Maintainer MEYER SEWER	MPCA License No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: 1000 K Pumped Tank 2: 1000 Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? The Second Transport of the pumped? The Second Transport of the pumped? The Second Transport of the pumped?	Total Gallons Pumped: 2000
Visual Inspection (note any problems with the	
	RECEIVED
	JAN 05 2016
	OVIE # 9 5010
	PIRICUEAGE
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width	in. X Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius	in. X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Lie	iquid Capacity Gallons / Tank Depth in. = Gallons/Inch
Sludge Level in. X Gallons Per Inch	= Sludge Volume Gallons
Scum Level in. X Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume/ Liq	quid Capacity = Percent Sludge and Scum in Tank %
Scum Layer Effluent Sludge Layer	*Tahks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.