

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

	System l	ocation		
Address 14810 Valley Cre	ek Tos		Telephone Number	
City Affra	State MN	ZIP 55001 Pro	perty ID No./GEO Code	
Owner Nathan Shan	Pumping Dat	7 7		
Contractor				
Maintainer MEYER SEWER	MPCA License	No. 915	Telephone Number 657.	459-016
What was done to the system?		Rep	ort Liquid Capacity in Gallor	IS
✓ Tank(s) Pumped		Tank 1: 1000	Pumped Tank 2: 1024	Pumped
Sludge and scum measured.		Tank 3:	Pumped Tank 4:	Pumped
Do tanks need to be pumped?		Total Gallons Pum	ped: 2000	
Yes No (If no provide measureme				
Visual Inspection (note any problems with	the system):	NOTE: This do	es not serve as a complian	ce inspection.
		L. V.T N/O Ware NO	T Dumnod	
*Tank Mea	surements-Use Un	ly If Tank(s) Were NO		
Tank Length in. X Tank Width	in. X Tank l	Depth in. =	: Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius	in. X 3.14	= Tank Volume (cu	bic inches)	
Tank Volume (cu. in.) / 231.01	Liquid Capacity	Gallons /	Tank Depth in. = Gallo	ns/Inch
	•	**************************************		<u></u>
Sludge Level in. X Gallons Per Inch	= Sludge '	Volume Gall	ons	:
Scum Level in. X Gallons Per Inch	= Scum V	olume Gall	ons	
Sludge Volume + Scum Volume	= Total Sli	udge and Scum Volun	ne Gallons	
<u> </u>	I Consider Community	- Daves	t Sludge and Scum in Tank	%
Total Sludge and Scum Volume	/ Liquid Capacity			
	Ħ		*Tanks must be pumped i	
			following conditions exist 1. The top of the sludge la	yer is less than
Scum Layer			12 inches from the bottor	n of the outlet
Effluent		ink Depth measured	baffle; or 2. Total sludge and scum	volume is greater
	Control of the Contro	om invert of outlet pe to bottom of tank	than 25 percent of the tar	nk's liquid
Sludge Layer		.	capacity.	
The state of the s	and the second s			
	Date	2 6 /	Reset	Form
Signature	Date	8/31/19	1,334	<u> </u>