

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

**GOVERNMENT CENTER** 

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

			Sys	tem Locatio	ın				
Address 897 Nordic Ave Cot			CHN	N		Telephone Number			
City Stillwets	r		State	W ZIP S	CASIA Pro	perty ID No./	GEO Code 3	7.11917.9	
Owner Michael	//.	Skjirvole	Pumpin		2/2	· ————————————————————————————————————	<i>U</i> 2	001100	
			· · · · · · · · · · · · · · · · · · ·	Contractor	0/13		· · · · · · · · · · · · · · · · · · ·	00.1	
Maintainer MEY	ER .	SEWER	MPCA Li	cense No.	915	Telephone N	Number 651	-459-016	
What was done to the system?				Report Liquid Capacity in Gallons					
Tank(s) Pumped				Tank 1: /Scoo Pumped Tank 2: Pumpec					
Sludge and scum measured.				i		Pumped			
Do tanks need to be pumped?				Tan					
Yes No (If no provide measurements below)				Total Gallons Pumped: 1500					
Visual Inspection	(note a	ny problems with	the system):	N	OTE: This do	es not serve	as a compliar	nce inspection	
		*Tank Meas	Iromonts.Use	Only 16 Tax	ik(s) Were NO	T Duran of			
			mements-ose	Only It Tan	K(s) Were NO	Pumped	· · · · · · · · · · · · · · · · · · ·		
Tank Length	in. <b>X</b> 	Tank Width	in, <b>X</b> T	ank Depth	in. =	Tank Volume	(cubic inches)		
Tank Radius	in. X	Tank Radius	in. 🗶 3	3.14 = Ta	nk Volume (cul	oic inches)			
Tank Volume (cu. in.	)	/ 231.01 =	Liquid Capa	city	Gallons /	Tank Depth	in. = Gallo	ns/Inch	
Sludge Level	in. X	Gallons Per Inch	= Siu	dge Volume	 Gallo	ns –	·	·	
Scum Level	in. <b>X</b>	Gallons Per Inch	= Scu	m Volume	Gallo	ns			
Sludge Volume	+	Scum Volume	= Tot	al Sludge and	d Scum Volume	<u> </u>	Gallons		
Total Sludge and Sci	um Volu	me/	Liquid Capac	ity	= Percent!	Sludge and Sc	um in Tank	%	
Scum Layer Effluent						*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or  2. Total sludge and scum volume is greated.			
Sludge Layer				pipe to bo	ttom of tank	than 25 percent of the tank's liquid capacity.			