

Signstura

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location System Location	
Address 14120 80th StS	Telephone Number
City Hostings State Mi	//ZIP 分分子 Property ID No./GEO Code
Owner Ivan Bake Pumping	, , , , , , , , , , , , , , , , , , ,
Contractor	
Maintainer MEYER SEWER MPCA Lice	ense No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: /saa Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below)	Total Gallons Pumped: 1500
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
RECEIVED	
JAN 07 2016	
	37.11. 3
*Tank Measurements-Use	Only If Tank(s) Were NOT Rumped HEALTH
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius in. X 3	.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. X Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Tota	I Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacit	ty = Percent Sludge and Scum in Tank %
Scum Layer Effluent Sludge Layer	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.

Date

Reset Form