

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

- 10		System	Location		
Address 227	16 ORWEll	Ct	J	Telephone Number	
City 5 fi//c	Nater	State/N/) ZIPSSOA 2Pro	pperty ID No./GEO Code	
Owner Tim	Press	Pumping Da	ate 11/27/15		
		Cont	tractor		
Maintainer MEY	ER SEWER	MPCA Licens	se No. 915	Telephone Number 651-459-016	
	vas done to the system?		Rep	ort Liquid Capacity in Gallons	
ank(s) Pumped			Tank 1: 1000 Pumped Tank 2: Pumper		
Sludge and scum measured.			Tank 3: Pumped Tank 4; Pumped		
Do tanks need to be pumped? Yes No (If no provide measurements below)			Total Gallons Pumped: 1000		
			L. Can Gallons Full	peu. 7000	
Visual inspection	(note any problems with	the system):	NOTE: This do	es not serve as a compliance inspection	
			•		
	*Tank Meas	urements-Use Or	nly If Tank(s) Were NO	「Pumped	
Tank Length	in. X Tank Width	in. X Tank	Depth in. =	Tank Volume (cubic inches)	
Tank Radius	in. X Tank Radius	in. X 3.14	4 = Tank Volume (cub	pic inches)	
Tank Volume (cu. in	/ 231.01 =	Liquid Capacity	Gallons /	Tank Depth in. = Gallons/Inch	
Sludge Level	in. X Gallons Per Inch	= Sludge	Volume Gallo	ons	
Scum Level	in. X Gallons Per Inch	= Scum V	/olume Gallo	ns	
Sludge Volume	+ Scum Volume	= Total SI	udge and Scum Volume	Gallons	
Total Sludge and Sc	cum Volume /	Liquid Capacity	= Percent	Sludge and Scum in Tank %	
		Ħ		*Tanks must be pumped if either of the	
				following conditions exist: 1. The top of the sludge layer is less than	
Scum Layer				12 inches from the bottom of the outlet	
Effluent			Tank Depth measured baffle; or 2. Total sludge and scum volume is gr		
<u></u>		- A 1	om invert of outlet ipe to bottom of tank	than 25 percent of the tank's liquid	
Sludge Layer				capacity.	
110			11/23/15		