

Cianatura

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006

Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

**System Location** 

Address 9535 53rd 54 N	Telephone Number
	te MN ZIP 5'5042, Property ID No./GEO Code
Owner Ali Vousset Pur	nping Date 10/13/15
Contractor	
Maintainer MEYER SEWER MPC	A License No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: /Soo A Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped?  Yes No (If no provide measurements below)	Total Gallons Pumped: \( \sum_{SOO} \)
Visual Inspection (note any problems with the syste	Pm): NOTE: This does not serve as a compliance inspection.
TO DESCRIPT DE STATEMENT DESCRIPTION OF STATEM	
RECEIVED	
JAN 07 2016	
*Tank Measurements Use Gnly II Tank is Were NOT Pumped	
Tank Length in. <b>X</b> Tank Width in.	X Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. <b>X</b> Tank Radius in.	X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. X Gallons Per Inch =	Sludge Volume Gallons
Scum Level in. <b>X</b> Gallons Per Inch =	Scum Volume Gallons
Sludge Volume + Scum Volume =	Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid C	apacity = Percent Sludge and Scum in Tank %
Scum Layer  Effluent  Sludge Layer	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than  12 inches from the bottom of the outlet baffle; or  2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.
	Date Recet Form

Data