

Cianatura

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006

Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 12021 St Coxx	7.5 Telephone Number
City Hus Lines State	e MM ZIP 55033 Property ID No./GEO Code
Owner Scott Quest's Pum	ping Date 10/12
Contractor	
Maintainer MEYER SEWER MPC.	A License No. 915 Telephone Number 651-459-016.
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: /Sour Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped?	Total Gallons Pumped:
Yes No (If no provide measurements below)	Total Gallotis Furniped.
Visual Inspection (note any problems with the system	m): NOTE: This does not serve as a compliance inspection.
RECEIVED	
JAN 0	·
PUBLIC HEALTH	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in,)	(Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in.)	(3.14 = Tank Volume (cubic inches)
The state of the s	
Tank Volume (cu, in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/inch	
Sludge Level in. X Gallons Per Inch =	Sludge Volume Gallons
Scum Level in. X Gallons Per Inch =	Scum Volume Gallons
Sludge Volume + Scum Volume =	Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Ca	apacity = Percent Sludge and Scum in Tank %
Scum Layer Effluent Sludge Layer	Tank Depth measured from invert of outlet pipe to bottom of tank "Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.

Data

Reset Form