

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

		System	Location			
Address 16762	Upper 15th S	75		Telephone Number		
City St Crois	Beach	State My/	ZIP 55043 Pro	perty ID No./GEO Code		
Owner Donns	Clark	Pumping Dat				
		Contr	actor			
Maintainer MEY	ER SEWER	MPCA License	No. 915	Telephone Number 65/-	459-016	
What was done to the system?			Report Liquid Capacity in Gallons			
Tank(s) Pumped			Tank 1: Pumped Tank 2: Coco Pumper			
Sludge and scum measured.			Tank 3: Pumped Tank 4: Pumped			
Do tanks need to be pumped? Yes Do (If no provide measurements below)			Total Gallons Pumped: 2000			
	(note any problems with			es not serve as a compliance	ce inspection	
	*Tank Mea	surements lee Onl	y If Tank(s) Were NO	Dumped		
Tank Langth						
Tank Length	in. X Tank Width	in, X Tank D	veptn in. =	Tank Volume (cubic inches)	,	
Tank Radius	in. 🗶 Tank Radius	in. X 3.14	= Tank Volume (cub	pic inches)		
Tank Volume (cu. in	.) / 231.01 :	= Liquid Capacity	Gallons /	Tank Depth in. = Gallon	is/Inch	
Sludge Levei	in. X Gallons Per Inch	= Sludge\	/olume Gallo	ns	,	
Scum Level	in. X Gallons Per Inch	= Scum Vo	olume Gallo	ns		
Sludge Volume	+ Scum Volume	= Total Slu	dge and Scum Volume	Gallons		
Total Sludge and Sc	um Volume	/ Liquid Capacity	= Percent	Sludge and Scum in Tank	%	
Scum Layer			*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet			
Effluent		fro	nk Depth measured m invert of outlet be to bottom of tank	baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid		
Sludge Layer				capacity.		