

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

		System Location			
Address 16599 2nd StN			Telephone Number		
City Lake kind State 11/21P 55043 Property ID No./GEO Code					
Owner Chad	Ehlers Pur	nping Date 1/1/1/15			
		Contractor			
Maintainer MEYE	ER SEWER MPC	A License No. 915	Telephone Number 651-4	59-0162	
What was done to the system?		Re	Report Liquid Capacity in Gallons		
Tank(s) Pumped		Tank 1: 1000 Pumped Tank 2: 1000 Pumper			
Sludge and scum measured.			Tank 3: 500 Pumped Tank 4; Pumped		
Do tanks need to be pumped? Yes No (If no provide measurements below)			Total Gallons Pumped: 2500		
Visual Inspection (r	note any problems with the syste	m): NOTE: This d	oes not serve as a compliance	inspection	
	*Tank Measurement	s-Use Only If Tank(s) Were NO	OT Pumped		
Tank Length	in. X Tank Width in.	χ Tank Depth in. :	= Tank Volume (cubic inches)		
Tank Radius	in. X Tank Radius in.	X 3.14 = Tank Volume (c	ubic inches)		
Tank Volume (cu. in.)	/ 231.01 = Liquid (Capacity Gallons	/ Tank Depthin, = Gallons/	nch	
Sludge Level	in. X Gallons Per Inch =	Sludge Volume Gal	lons		
Scum Level	in. X Gallons Per Inch =	Scum Volume Gal	lons		
Sludge Volume	+ Scum Volume =	Total Sludge and Scum Volur	ne Gallons		
Total Sludge and Scu	m Volume / Liquid C	apacity = Percen	t Sludge and Scum in Tank	%	
		*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than			
Scum Layer	1 (2 2 2)		12 inches from the bottom of		
Effluent		Tank Depth measured from invert of outlet pipe to bottom of tank baffle; or 2. Total sludge and scum volume is great than 25 percent of the tank's liquid			
Sludge Layer		Pipe to bottom or tank	capacity.		