

Signature

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 210 Indian Trail 5	Telephone Number
	tate MW ZIP Score Property ID No./GEO Code
Owner Leff Bredg Pumping Date 10/1/15	
Contractor	
Maintainer MEYER SEWER M	PCA License No. 915 Telephone Number 651-459-016.
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: 1500 Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? The second of the pumped?	Total Gallons Pumped: 15000
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
RECEIVED	
JAN 06 2016	
JAN 00 2010	
PUBLIC HEALTH	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in.	. X Tank Depth in. = Tank Volume (cubic inches)
	X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid	d Capacity Gallons / Tank Depth in. = Gallons/Inch
Sludge Level in. X Gallons Per Inch	= Sludge Volume Gailons
Scum Level in. X Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid	Capacity = Percent Sludge and Scum in Tank %
Scum Layer Effluent Sludge Layer	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.

Date

Reset Form