

Signature

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location System Location			
Address 15169 Afton Bluck.	S.		Telephone Number
		IP5500/ Prop	perty ID No./GEO Code
Owner Donald LEE	Pumping Date	10/1/15	
Contractor			
Maintainer MEYER SEWER	MPCA License N	10. 915	Telephone Number 651-459-016
What was done to the system?		Repo	rt Liquid Capacity in Gallons
Tank(s) Pumped 2		Tank 1: /250	Pumped Tank 2: 1250 Pumped
Sludge and scum measured. Do tanks need to be pumped?		Tank 3:	Pumped Tank 4: Pumped
Yes No (If no provide measurements belo	ow)	Total Gallons Pump	ed: <u>2500</u>
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.			
RECEIVED			
· -			
• JAN 06 2016			
PUBLICHEALTH			
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped			
	n. X Tank De		Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)			
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch			
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons			
Scum Level in. X Gallons Per Inch = Scum Volume Gallons			
Sludge Volume + Scum Volume	Total Slud	ge and Scum Volume	Gallons
Total Sludge and Scum Volume / Liqu	id Capacity —	= Percent :	Sludge and Scum in Tank
7	П		*Tanks must be pumped if either of the following conditions exist:
	= 4		1. The top of the sludge layer is less than
Scum Layer The Company of the Compan	}	12 inches from the bottom of the outlet baffle; or	
Effluent	from	c Depth measured n invert of outlet	2. Total sludge and scum volume is greate: than 25 percent of the tank's liquid
Sludge Layer .	pipe	pipe to bottom of tank capacity.	
	arconnector and		

Date 10/1/15

Reset Form