

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location					
Address 10417	7-	Telephone Number			
City Co Hape	Cores Cloud T.	StateMA ZIP	55016 Pro	perty ID No./GEO Code	
Owner Scott	Dirtzu	Pumping Date &	11		
Contractor					
Maintainer MEY	RSEWER	MPCA License No.	915	Telephone Number 65/-	459-016
What wa		Report Liquid Capacity in Gallons			
Tank(s) Pumped	7	Tank 1: 1500	Pumped Tank 2:	Pumped	
Sludge and scum  Do tanks need to		Tank 3:	Pumped Tank 4:	Pumped	
	elow)	Total Gallons Pumped: 15 00			
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.					
-		<i>;</i>			
	9107 <b>90</b> NVC				
	JECEINED				
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped					
Tank Length	in. <b>X</b> Tank Width	in. <b>X</b> Tank Dept	h in. =	Tank Volume (cubic inches)	
Tank Radius	in. <b>X</b> Tank Radius	in. X 3.14 =	Tank Volume (cul	bic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch					
Sludge Level	in. <b>X</b> Gallons Per Inch	= Sludge Volu	me Gallo	ons	
Scum Level	in. <b>X</b> Gallons Per Inch	= Scum Volum	ne Gallo	ons	
Sludge Volume	+ Scum Volume	= Total Sludge	and Scum Volum	e Gallons	
Total Sludge and Scu	m Volume / Lic	uid Capacity	= Percent	Sludge and Scum in Tank	%
Scum Layer				*Tanks must be pumped if e following conditions exist:  1. The top of the sludge layers the hotters.	er is less than
		Tank	enth measured	12 inches from the bottom baffle; or	
Effluent	-	from in	from invert of outlet pipe to bottom of tank pipe ta		
Sludge Layer				сарасну.	