

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730 /

## SSTS MAINTENANCE REPORT

System Location System Location	
Address 483 Jules Ave.	Telephone Number
City Lake Elmo	StateMW ZIPS5042 Property ID No./GEO Code
Owner Craig Rossow	Pumping Date 10/12/15
Contractor	
Maintainer MEYER SEWER	MPCA License No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Pank(s) Pumped 2	Tank 1: 1500 Pumped Tank 2: 1000 Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped?  Tyes No (If no provide measurements bel	ow) Total Gallons Pumped: 2500
Visual Inspection (note any problems with the s	system): NOTE: This does not serve as a compliance inspection.
JAN 06 2016	
L PUBLIC HEALTH	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width	in. X Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius	in. X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. <b>X</b> Gallons Per Inch	= Sludge Volume Gallons
Scum Level in. <b>X</b> Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
Scum Layer  Effluent  Sludge Layer	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than  12 inches from the bottom of the outlet baffle; or  2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.

Reset Form