

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location				
Address 1090 Paris AUE. Ct.	N.		Telephone Number	
	eMW ZIPZ	55082 Prope	erty ID No./GEO Code	
Owner Brad WillErt Pumping Date 10/9/15				
Contractor				
Maintainer MEYER SEWER MPC	A License No.	915	Telephone Number 651-45	9-016
What was done to the system?	[Repor	t Liquid Capacity in Gallons	
Tank(s) Pumped 2	Ta	ank 1: 1250 &	Pumped Tank 2: 1250K	bPumped
Sludge and scum measured.	1	·	Pumped Tank 4:	Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below)	T	otal Gallons Pumpe	d: 2500	
	L_			
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.				
RECEIVED				
JAN 06 2016				
2010				
PUBLIC HEALT				
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped				
Tank Length in. X Tank Width in. X	(Tank Depth	in. =	Fank Volume (cubic inches)	
Tank Radius in. 🗶 Tank Radius in. 🕽	(3.14 =)	Tank Volume (cubic	inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch				
Sludge Level in. X Gallons Per Inch =	Sludge Volun	ne Gallon	S	
Scum Level in. X Gallons Per Inch =	Scum Volume	Gallon	S	
			Gallons	
Sludge Volume + Scum Volume =	Total Sludge	and Scum Volume		
Total Sludge and Scum Volume / Liquid Ca	pacity	= Percent SI	udge and Scum in Tank	%
Scum Layer Effluent Sludge Layer	from inv	epth measured vert of outlet bottom of tank	*Tanks must be pumped if either following conditions exist: 1. The top of the sludge layer is 12 inches from the bottom of the baffle; or 2. Total sludge and scum volum than 25 percent of the tank's lique capacity.	less than ie outl e t e is greatei
Cianatura IIII	Data 10	1/15	Reset Form	