

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location			
Address 44/0 McDonald Dr.	C+. N.	Telephone Number	
City Stillwater State M	W ZIP55082 Proj	perty ID No./GEO Code	
Owner Jim RUSSOW Pumping	Date 10/22/15		
C	ontractor		
Maintainer MEYER SEWER MPCALic	ense No. 915	Telephone Number 651-4	59-016
What was done to the system?	Repo	ort Liquid Capacity in Gallons	
☐ Tank(s) Pumped	Tank 3: [Pumped Tank 2: 1000 Pumped Tank 4: ped: 2000 es not serve as a compliance	Pumped
*Tank Measurements-Use	Only If Tank(s) Were NO	Pumped	
Tank Length in. X Tank Width in. X Ta	in. =	Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius in. X 3	.14 = Tank Volume (cub	pic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capad	city Gallons /	Tank Depthin. = Gallons.	/Inch
Sludge Level in. X Gallons Per Inch = Slud	dge Volume Gallo	ns .	
Scum Level in. X Gallons Per Inch = Scu	m Volume Gallo	ns	
Sludge Volume + Scum Volume = Tot	al Sludge and Scum Volume	e Gallons	
Total Sludge and Scum Volume / Liquid Capac	ty = Percent	Sludge and Scum in Tank	%
Scum Layer Effluent Sludge Layer	Tank Depth measured from invert of outlet pipe to bottom of tank	*Tanks must be pumped if elfollowing conditions exist: 1. The top of the sludge laye 12 inches from the bottom of baffle; or 2. Total sludge and scum volthan 25 percent of the tank's capacity.	r is less than of the outlet Tume is greater
	10 100	Reset Fo	