

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location

Address 0320 Lake Jane	Trail Telephone Number
City Lake Elmo Stat	te MW ZIP 55042 Property ID No./GEO Code
Owner Pat Jennings Pumping Date 10/9/15	
Contractor /	
Maintainer MEYER SEWER MPC	A License No. 915 Telephone Number 651-459-016.
What was done to the system?	Report Liquid Capacity in Gallons
Pank(s) Pumped	Tank 1: /500 Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Tyes No (If no provide measurements below)	Total Gallons Pumped: 1500
Visual Inspection (note any problems with the syste	m): NOTE: This does not serve as a compliance inspection.
JAM 06 7016	
	DUBLIC HEALTH
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. X Gallons Per Inch =	Sludge Volume Gallons
Scum Level in. X Gallons Per Inch =	Scum Volume Gallons
Sludge Volume + Scum Volume =	Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
Scum Layer Effluent Sludge Layer	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greated than 25 percent of the tank's liquid capacity.
Signature	10/9/15 Reset Form