

Cianotura

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location

Address 8592 Francisco Tell	Telephone Number
City Lake Elmo State	W ZIP SSORD Property ID No./GEO Code
Owner Enie Kaush/ Pumping Date 6/3/5	
Contractor	
Maintainer MEYER SEWER MPCALice	ense No. 915 Telephone Number 651-459-016.
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped Sludge and scum measured. Do tanks need to be pumped? Yes No (If no provide measurements below)	Tank 1: Pumped Tank 2: Pumped Tank 3: Pumped Tank 4: Pumped Total Gallons Pumped: 1200
Visual Inspection (note any problems with the system):	NOTE: This does not serve as a compliance inspection.
	JAN 07 JIS
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius in. X 3	.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. X Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Tota	al Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
Scum Layer Effluent Sludge Layer	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.

Data

Reset Form