

DEPARTMENT OF PUBLIC MEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

| System Location | |
|--|--|
| Address 11695 Lockridge the 1 | Telephone Number |
| | eMM ZIPGGOBZ Property ID No./GEO Code |
| | ping Date 60/23/15 |
| | Contractor |
| Maintainer MEYER SEWER MPC | A License No. 915 Telephone Number 651-459-014 |
| What was done to the system? | Report Liquid Capacity in Gallons |
| Tank(s) Pumped | Tank 1: 1266 Pumped Tank 2: Pumper |
| Sludge and scum measured. | Tank 3: Pumped Tank 4: Pumped |
| Do tanks need to be pumped? | |
| Yes No (If no provide measurements below) | |
| Visual Inspection (note any problems with the system | |
| | |
| | 3A., 97 1036 |
| | |
| | |
| *Tank Measurements-Use Only If Tank(s) Were NOT Pumped | |
| Tank Length in. X Tank Width in.) | (Tank Depth in. = Tank Volume (cubic inches) |
| Tank Radius in. X Tank Radius in.) | (3.14 = Tank Volume (cubic inches) |
| Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch | |
| Sludge Level in. X Gallons Per Inch = | Sludge Volume Gallons |
| Scum Level in. X Gallons Per Inch = | Scum Volume Gallons |
| Sludge Volume + Scum Volume = | Total Sludge and Scum Volume Gallons |
| Total Sludge and Scum Volume / Liquid Ca | apacity = Percent Sludge and Scum in Tank % |
| Scum Layer Effluent Sludge Layer | *Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity. |