

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

		System L	ocation		
Address 602	Quixote AUE.	N		Telephone Number	
City Lake lon			ZIP55047 Pro	operty ID No./GEO Code	
Owner Nicols	Nond	Pumping Date			
		Contra	actor		
Maintainer MEY	ER SEWER	MPCA License	No. 915	Telephone Number 651-459-016	
What was done to the system?			Report Liquid Capacity in Gallons		
PTank(s) Pumped 2			Tank 1: 1000	Pumped Tank 2: 1000 Pumpery	
Sludge and scum measured. Do tanks need to be pumped?			Tank 3: Pumped Tank 4: Pumpeo		
Yes No (If no provide measurements below)			Total Gallons Pumped: 2000		
	note any problems with (NOTE: This do	es not serve as a compliance inspection	
			·		
	*Tank Meası	rements-Use Only	/ If Tank(s) Were NO	T Pumped	
Tank Length	in. X Tank Width	in. X Tank D	epth in. =	Tank Volume (cubic inches)	
Tank Radius	in. X Tank Radius	in. X 3.14	= Tank Volume (cu	bic inches)	
Tank Volume (cu. in.)	/ 231.01 =	Liquid Capacity	Gallons /	Tank Depthin. = Gallons/Inch	
Sludge Level	in. X Gallons Per Inch	= Sludge V	olume Gallo	oris	
Scum Level	in. X Gallons Per Inch	= Scum Vo	lume Galk	ons	
Sludge Volume	+ Scum Volume	= Total Slu	dge and Scum Volum	e Gallons	
Total Sludge and Scu	m Volume /	Liquid Capacity	= Percent	Sludge and Scum in Tank %	
		<u> </u>		*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than	
Scum Layer			12 inches from the bottom of the outlet		
Effluent		fror	Tank Depth measured from invert of outlet pipe to bottom of tank baffle; or 2. Total sludge and scum volume is great than 25 percent of the tank's liquid		
Sludge Layer		- Pib	E to bottom of tank	capacity.	
-			in bole		