

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

		Syst	tem Location			
Address 14589	65th St	5		Telephone Number		
City Hasting	5	State	W ZIP 55033 Pri	operty ID No./GEO Code		
Owner Aline	kluge	Pumping	Date 19 30 15			
			ontractor			
Maintainer MEY	ER SEWER	MPCA Lic	ense No. 915	Telephone Number 65/	-459-016	
What w	vas done to the syster	m?	Rep	ort Liquid Capacity in Gallor	ns	
📈 Tank(s) Pumped			Tank 1: 1500 & Pumped Tank 2: (coes Pumper)			
Sludge and scum measured.			Tank 3: Pumped Tank 4: Pumped Total Gallons Pumped: 2500			
Do tanks need to be pumped? Yes Do (If no provide measurements below)						
			(
visual inspection	(note any problems	with the system):	NOTE: This do	es not serve as a compliar	ice inspectior	
,						
	*Tank	Measurements-Use	Only If Tank(s) Were NO	T Pumped		
Tank Langeth				**************************************		
Tank Length	in. X Tank Width	1D, X 18	ank Depth in. =	Tank Volume (cubic inches)		
Tank Radius	in. 🗶 Tank Radius	in. X 3	3.14 = Tank Volume (cu	bic inches)		
Tank Volume (cu. in	/ 231.	01 = Liquid Capac	city Gallons /	Tank Depth in. = Gallo	ns/Inch	
Sludge Level	in. X Gallons Per I	nch = Sluc	dge Volume Gall	ons		
Scum Level	in. X Gallons Per I	nch = Scu	m Volume Galle	ons		
Sludge Volume	— + Scum Volum	se = Tota	al Sludge and Scum Volum	_{se} Gallons		
Total Sludge and So				gel er-	%	
Total sludge and St		/ Liquid Capaci	- Percent	Sludge and Scum in Tank		
		1		*Tanks must be pumped i		
				following conditions exist 1. The top of the sludge la		
Scum Layer				12 inches from the botton	n of the outlet	
Effluent			Tank Depth measured from invert of outlet	baffle; or 2. Total sludge and scum v	tle; or otal sludge and scum volume is greate	
Chidas			pipe to bottom of tank	than 25 percent of the tank's liquid capacity.		
Sludge Layer				capacity.		
-	12.50					