

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 170 BEUMS Lane	Telephone Number
CityMantomedi StateMN Z	IP55//5 Property ID No./GEO Code
Owner Joseph Beulns Pumping Date 10/22/15	
Contractor	
Maintainer MEYER SEWER MPCA License N	lo. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: 1000 Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below)	Total Gallons Pumped: 1000
Visual Inspection (note any problems with the system):	NOTE: This does not serve as a compliance inspection
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank De	pth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14 =	= Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. X Gallons Per Inch = Scum Volume Gallons	
	C. II
Sludge Volume + Scum Volume = Total Slud	ge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity	= Percent Sludge and Scum in Tank %
	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than
Scum Layer 1	12 inches from the bottom of the outlet
	invert of outlet 2. Total sludge and scum volume is greate:
	to bottom of tank than 25 percent of the tank's liquid capacity.