

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

**GOVERNMENT CENTER** 

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

Address 16789 194h 54	System Location Telephone Number
	State MN ZIP5504 7 Property ID No./GEO Code
1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
Owner Nicole Corn	Pumping Date 7/28//5
Maintainer MEYER SEWER	MPCA License No. 915 Telephone Number 651-459-016
	Report Liquid Capacity in Gallons
What was done to the system?	
☐ Sludge and scum measured.	Idik 1. 1000 12 . Idik 2.
Do tanks need to be pumped?	Tank 3: Pumped Tank 4: Pumped
Yes No (If no provide measurements be	elow) Total Gallons Pumped: 1000
Visual Inspection (note any problems with the	NOTE: This does not serve as a compliance inspection.
*Tank Measurer	ments-Use Only If Tank(s) Were NOT Pumped
Tank Length in. X Tank Width	in. X Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. 🗶 Tank Radius	in. X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. <b>X</b> Gallons Per Inch	= Sludge Volume Gallons
Scum Level in. <b>X</b> Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liq	quid Capacity — Percent Sludge and Scum in Tank — %
Scum Layer  Effluent  Sludge Layer	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.
Signature All	Date 7/28/15 Reset Form