

Signature ///

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

The second secon

System Location	
Address 15281 19th St. Ct. N	Telephone Number
	ZIP 55082 Property ID No./GEO Code
Owner /(EVI) 1+aba 5 Pumping Da	te 8/6/15 —
Contractor	
Maintainer MEYER SEWER MPCA Licens	e No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped 2	Tank 1: 1250 Pumped Tank 2: 1250 Pumped
Sludge and scum measured. Do tanks need to be pumped?	Tank 3: Pumped Tank 4: Pumped
Yes No (If no provide measurements below)	Total Gallons Pumped: 2500
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
	No.
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank	Depth in. = Tank Volume (cubic inches)
	= Tank Volume (cubic inches)
	,
Tank Volume (cu. in.) / 231.01 = Liquid Capacity	Gallons / Tank Depth in. = Gallons/Inch
Sludge Level in. X Gallons Per Inch = Sludge	Volume Gallons
Scum Level in. X Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Total Sl	udge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
	*Tanks must be numbed if either of the
	*Tanks must be pumped if either of the following conditions exist:
Scum Layer	1. The top of the sludge layer is less than 12 inches from the bottom of the outlet
	nk Depth measured baffle; or 2. Total sludge and scum volume is greater
pi	than 25 percent of the tank's liquid
Sludge Layer	capacity.

Reset Form