

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location System Location	
Address 6066 Inwood Ct. Y	Telephone Number
City Stillwater State MN Z	IP 5508 Property ID No./GEO Code
Owner Joseph Kelly Pumping Date 11/5/15	
Contractor /	
Maintainer MEYER SEWER MPCA License N	o. 915 Telephone Number 651-457-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: 1000 Pumped Tank 2: 1000 Pumped
Sludge and scum measured.  Do tanks need to be pumped?	Tank 3: Pumped Tank 4: Pumped
Yes No (If no provide measurements below)	Total Gallons Pumped: 2000
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank Der	oth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu, in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in: X Gallons Per Inch = Scum Volume Gallons	
Słudge Volume + Scum Volume = Total Słudg	ge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
from	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than  12 inches from the bottom of the outlet baffle; or  2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.