

Signature \_\_\_\_

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

**GOVERNMENT CENTER** 

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location	
Address 48 1430 Quens Aues	Telephone Number
	ZIP SSG42, Property ID No./GEO Code
Owner Windows Schote Pumping Date	8/20/15
Contra	
Maintainer MEYER SEWER MPCA License	No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Zank(s) Pumped	Tank 1: South Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped?  Tes No (If no provide measurements below)	Total Gallons Pumped: 1506
Visual Inspection (note any problems with the system):	NOTE: This does not serve as a compliance inspection.
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. <b>X</b> Tank Width in. <b>X</b> Tank D	pepth in. = Tank Volume (cubic inches)
	= Tank Volume (cubic inches)
College/Inch	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch	
Sludge Level in. <b>X</b> Gallons Per Inch = Sludge \	olume Gallons
Scum Level in. <b>X</b> Gallons Per Inch = Scum Vo	olume Gallons
Sludge Volume + Scum Volume = Total Slu	idge and Scum Volume Gallons
	= Percent Sludge and Scum in Tank %
Total Sludge and Scum Volume / Liquid Capacity -	
	*Tanks must be pumped if either of the following conditions exist:
	1. The top of the sludge layer is less than
Scum Layer III	12 inches from the bottom of the outlet
	hk Depth measured baffle; or 2. Total sludge and scum volume is greater
fro	than 25 percent of the tank's liquid
Sludge Layer	capacity.

Date

Reset Form