

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

**GOVERNMENT CENTER** 

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

		System Location		
Address 11459 60th 57. N			Telephone Number	
City L	Still water State	MW ZIP 550 87 Pr	operty ID No./GEO Code	
Owner Chad		ping Date ///25/15		
		Contractor		
Maintainer MEY	ER SEWER MPCA	License No. 915	Telephone Number 651-459-016	
What was done to the system?		Rep	Report Liquid Capacity in Gallons	
Tank(s) Pumped	4	Tank 1: /////	Tank 1: 1000 Pumped Tank 2: 1000 Pumped	
Sludge and scun	•		Pumped Tank 4: 1000 Pumperd	
Do tanks need to	· · · · · · · · · · · · · · · · · · ·			
Yes N	lo (If no provide measurements below)	Total Gallons Pum	Total Gallons Pumped: 4000	
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection			es not serve as a compliance inspection	
	*Tank Measurements-	Use Only If Tank(s) Were NO	T Pumped	
Tank Length	in. X Tank Width in. X	Tank Depth in. =	Tank Volume (cubic inches)	
Tank Radius	in. χ Tank Radius in. χ	3.14 = Tank Volume (cu	bic inches)	
Tank Volume (cu. in	/ <b>231.01</b> = Liquid Ca	apacity Gallons /	Tank Depthin. = Gallons/Inch	
Sludge Level	in. <b>X</b> Gallons Per Inch =	Sludge Volume Gall	ons	
Scum Level	in. <b>X</b> Gallons Per Inch =	Scum Volume Galle	ons	
Sludge Volume	+ Scum Volume =	Total Sludge and Scum Volum	e Gallons	
Total Sludge and Sc	cum Volume / Liquid Ca	pacity = Percent	Sludge and Scum in Tank %	
	,:		*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than	
Scum Layer		<u> </u>	12 inches from the bottom of the outlet	
Effluent		Tank Depth measured from invert of outlet	from invert of outlet  2. Total sludge and scum volume is greated than 35 percent of the tank's liquid	
Sludge Layer		pipe to bottom of tank	capacity.	
/	14 14	1/25/15		