

DEPARTMENT OF PUBLIC MEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006

Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location System Location					
Address 7540	Military Ro	ad		Telephone Number	
City Noo	dbury	State W	N ZIP 55/29 Pro	pperty ID No./GEO Code	
Owner Duane	Bradley	Pumping I	·		
	8	Co	ntractor		
Maintainer MEY	R SEWER	MPCA Lice	nse No. 915	Telephone Number 65/	457-016
What wa	s done to the system?		Report Liquid Capacity in Gallons		
Tank(s) Pumped			Tank 1: 1000	Pumped Tank 2: 1000	Q-Pumper
Sludge and scum measured. Do tanks need to be pumped?			Tank 3:	Pumped Tank 4;	Pumper
Yes No (If no provide measurements below)			Total Gallons Pumped: 2000		
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection					
	*Yank Mage	Tomask Had	Only If Tank(s) Were NO		
		rements-use (only if Tank(s) were NO	l Pumpea	
Tank Length	in. X Tank Width	in. 🗶 Tan	in. =	Tank Volume (cubic inches)	PP-2-2-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1
Tank Radius	in. 🗶 Tank Radius	in. X 3.	14 = Tank Volume (cul	oic inches)	
Tank Volume (cu. in.)	/ 231.01 =	Liquid Capacit	y Gallons/	Tank Depth in. = Gallor	ns/inch
Sludge Level	in. X Gallons Per Inch	= Sludg	ge Volume Gallo	ons	passari i inga matan pas
Scum Level	in. X Gallons Per Inch	= Scum	Volume Gallo	ons	
Sludge Volume	+ Scum Volume	= Total	Sludge and Scum Volum	e Gallons	
Total Sludge and Scu	m Volume /	Liquid Capacity	= Percent	Sludge and Scum in Tank	95
Scum Layer Effluent Sludge Layer			Tank Depth measured from invert of outlet pipe to bottom of tank	*Tanks must be pumped if following conditions exist: 1. The top of the sludge lay 12 inches from the bottom baffle; or 2. Total sludge and scum v than 25 percent of the tank capacity.	ver is less than of the outlet