

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

**GOVERNMENT CENTER** 

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

		System Location	· · · · · · · · · · · · · · · · · · ·
Address 3843	Oukgreen Ave	3.0	Telephone Number
City Stillwater State MW ZIPS5032 Property ID No./GEO Code			
Owner Kath	Worton	Pumping Date 1/127/15	
		Contractor	
Maintainer MEY	ER SEWER	MPCA License No. 915	Telephone Number 651-459-016
What w	as done to the system?	Re	port Liquid Capacity in Gallons
Tank(s) Pumped / Sludge and scum measured. Do tanks need to be pumped? Yes No (If no provide measurements below)		Tank 3:	Pumped Tank 2: Pumped Pumped Tank 4: Pumped
Visual inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection			
	*Tank Measurem	ents-Use Only If Tank(s) Were No	OT Pumped
Tank Length	in. 🗶 Tank Width	in. <b>X</b> Tank Depth in. :	= Tank Volume (cubic inches)
Tank Radius	in. <b>X</b> Tank Radius	in. <b>X 3.14 =</b> Tank Volume (c	ubic inches)
Tank Volume (cu. in.	/ <b>231.01</b> = Liq	uid Capacity Gallons	/ Tank Depth in. = Gallons/Inch
Sludge Level	in. <b>X</b> Gallons Per Inch	= Sludge Volume Gal	lons
Scum Level	in. <b>X</b> Gallons Per Inch	= Scum Volume Gal	lons
Sludge Volume	+ Scum Volume	= Total Sludge and Scum Volum	me Gallons
Total Sludge and Sc	um Volume / Liqu	id Capacity = Percer	at Sludge and Scum in Tank%
Scum Layer  Effluent  Sludge Layer		Tank Depth measured from invert of outlet pipe to bottom of tank	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or  2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.
Scum Level Sludge Volume Total Sludge and Sc Scum Layer Effluent	in. <b>X</b> Gallons Per Inch + Scum Volume	= Scum Volume Gal = Total Sludge and Scum Volume  iid Capacity = Percen  Tank Depth measured from invert of outlet	de Gallons  Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less tha 12 inches from the bottom of the outle baffle; or  2. Total sludge and scum volume is greathan 25 percent of the tank's liquid