

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

		System Locati	on			
Address 14703	Hudson Rols			Telephone Number		
City Afton		State MAJZIP	5001 P	roperty ID No./GEO Code	1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	
Owner Rox	Post het	Pumping Date //	16/10			
		Contractor	<i>u/:</i> 3	<u></u>		
Maintainer ME	ER SEWER	MPCA License No.	915	Telephone Number 65	1-459-016	
What was done to the system?			Report Liquid Capacity in Gallons			
Tank(s) Pumped	}	Ta	nk 1: /5/20	Pumped Tank 2:	Pumpe()	
Sludge and scum measured.			nk 3;	Pumped Tank 4;	Pumped	
Do tanks need to be pumped? Yes No (If no provide measurements below)			tal Gallons Pur	mped: <i>150</i> 0		
	(note any problems with the			loes not serve as a complia	nce inspection	
		,				
	*Tank Measu	rements-Use Only If Ta	nk(s) Were N	OT Pumped		
Tank Length	in. X Tank Width	in. X Tank Depth	in. :	= Tank Volume (cubic inches	3)	
Tank Radius	in. X Tank Radius	in. X 3.14 = T	ank Volume (c	ubic inches)		
Tank Volume (cu. ir	n.) / 231.01 =	Liquid Capacity	Gallons	/ Tank Depthin. = Gall	ons/Inch	
Sludge Level	in. X Gallons Per Inch	= Sludge Volum	e Gal	llons		
Scum Level	in. X Gallons Per Inch	= Scum Volume	Gal	lons		
Sludge Volume	+ Scum Volume	= Total Sludge a	nd Scum Volur	me Gallons		
Total Sludge and S	cum Volume / I	Liquid Capacity	= Percer	at Sludge and Scum in Tank	%	
Scum Layer Effluent Sludge Layer			oth measured ert of outlet	*Tanks must be pumped following conditions exist 1. The top of the sludge 12 inches from the botto baffle; or 2. Total sludge and scum than 25 percent of the ta	st: layer is less than om of the outlet volume is greats	