

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

the second second second second	1.22			System Loca	ition		
Address 594/a	<u> </u>	Fawn "	Trail	PiRC	/5	Telephone Number	
City 11 Dood		11			55125 P	Property ID No./GEO Code	
Owner Enik F	-	chosts	······································	ping Date	7/10/18		
- Company of the Comp	77	<u> </u>		Contracto	/ 		
Maintainer MEYE	FR &	EWER	MPC	A License No	915	Telephone Number 65	51-459-016
		to the system?			Re	port Liquid Capacity in Ga	llons
Tank(s) Pumped	/			-	Tank 1: /5 /37)	Pumped
Sludge and scum measured.							
Do tanks need to be pumped?							
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.							
					·		
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped							
Tank Length	in. X	Tank Width	in. X	Tank Dept	h in. :	= Tank Volume (cubic inch	es)
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)							
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch							
Sludge Level	in. X	Gallons Per Inch		Sludge Volur	ne Gal	llons	
Scum Level	in. X	Gallons Per Inch	=	Scum Volum	e Gal	llons	
Sludge Volume	+	Scum Volume	=	Total Sludge	and Scum Volur	me Gallons	
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %							
	_					*Tanks must be pumpe	d if either of the
						following conditions ex 1. The top of the sludge	
Scum Layer						12 inches from the bott	
Effluent				5	epth measured	baffle; or 2. Total sludge and scu	m volume is greater
				Ħ	vert of outlet bottom of tank	than 25 percent of the	
Sludge Layer						capacity.	··.
		1					
Signature /	1//			Date	7/10/1	S Res	et Form