

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

City Stillustry Owner Lowise Gross Pumping Date 1/3/5 Contractor Maintainer MEYER SEWER MPCA License No. 915 What was done to the system? Report Tank 1: 1000	elephone Number ty ID No./GEO Code elephone Number 651-459-0162 Liquid Capacity in Gallons
City Stillusty Owner Lowise Gross Pumping Date 1/3/5 Contractor Maintainer MEVER SEWER MPCA License No. 915 What was done to the system? Proper Report Sludge and scum measured.	elephone Number 651–459–016 Liquid Capacity in Gallons
Contractor Maintainer MEYER SEWER MPCA License No. 915 Te What was done to the system? Report Tank 1: 1000	Liquid Capacity in Gallons
Maintainer MEVER SEWER MPCA License No. 915 Te What was done to the system? Report Tank 1: 1000 Telephone Sludge and scum measured.	Liquid Capacity in Gallons
What was done to the system? Report ☐ Tank 1: 1000 ☐ ☐ Sludge and scum measured.	Liquid Capacity in Gallons
Tank(s) Pumped Tank 1: 1000 Tank 1: 1000 Tank 2: Tank 3: T	
Sludge and scum measured.	,
Sludge and scum measured.	Pumped Tank 2: X Pumper
0	Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below) Total Gallons Pumped	: 200
	not serve as a compliance inspection
note. This does	Tot Serve as a compliance respection
*Tank Measurements-Use Only If Tank(s) Were NOT Pu	Imped
Tank Length in. X Tank Width in. X Tank Depth in. = Ta	ink Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic i	inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tar	nk Depth in. = Gallons/Inch
Studge Level in. X Gallons Per Inch = Studge Volume Gallons	
Scum Level in. X Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Total Sludge and Scum Volume	Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Slud	dge and Scum in Tank %
Scum Layer Effluent Tank Depth measured from invert of outlet pipe to bottom of tank	Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.