

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

	System Location
Address 14901 1149h 54	Telephone Number
City Stillwater	State MN ZIP 5508 Property ID No./GEO Code
owner Don Oszland	Pumping Date 7 /23 / 15
	Contractor Contractor
Maintainer MEYER SEWER	MPCA License No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped 2	Tank 1: 1250 Pumped Tank 2: 1250 Pumped
Sludge and scum measured. Do tanks need to be pumped?	Tank 3: Pumped Tank 4: Pumped
Yes No (If no provide measurements b	Total Gallons Pumped: 2500
Visual Inspection (note any problems with the	e system): NOTE: This does not serve as a compliance inspection.
*Tank Measure	ments-Use Only If Tank(s) Were NOT Pumped
Tank Length in. X Tank Width	in. X Tank Depth in. = Tank Volume (cubic inches)
	in. X 3.14 = Tank Volume (cubic inches)
	-
Tank Volume (cu. in.) / 231.01 = ц	iquid Capacity Gallons / Tank Depth in. = Gallons/Inch
Sludge Level in. X Gallons Per Inch	= Sludge Volume Gallons
Scum Level in. X Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Lic	quid Capacity = Percent Sludge and Scum in Tank %
	*Tanks must be pumped if either of the
	following conditions exist:
Scum Layer	1. The top of the sludge layer is less than 12 inches from the bottom of the outlet
Effluent	Tank Depth measured baffle; or
	pipe to bottom of tank than 25 percent of the tank's liquid
Sludge Layer	capacity.
A A	
//0 ///	