

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

		System	Location	T.C.
Address ///35	- 142 Nd 54	, N		Telephone Number
city Still Wa	ter	State M v	ZIP55082 Pro	pperty ID No./GEO Code
Owner Ron Pierce Pumping Date 7 23/15				
Contractor				
Maintainer MEYER SEWER MPCA License No. 915 Telephone Number 651-459-016				
What was done to the system? Tank(s) Pumped Sludge and scum measured. Do tanks need to be pumped? Yes No (If no provide measurements below) Visual Inspection (note any problems with the system):			Tank 1: /250 Tank 3: Total Gallons Pum	Pumped Tank 2: ASO Pumped Pumped Tank 4: Pumped ped: ASOO es not serve as a compliance inspection.
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped				
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)				
Tank Radius	in. 🗶 Tank Radius	in. X 3.14	= Tank Volume (cul	pic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch				
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons				
Scum Level in. X Gallons Per Inch = Scum Volume Gallons				
	-			- n
Sludge Volume	+ Scum Volume 	= Total Slu	idge and Scum Volume	Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %				
Scum Layer = Effluent Sludge Layer		fro	nk Depth measured m invert of outlet be to bottom of tank	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.
Signature		Date	7/23/15	Reset Form