

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 10453 Theres Cloud Mr.	Telephone Number
City Collace Laore State MN	ZIP 550/6 Property ID No./GEO Code
Owner Dorothy Dirthy Pumping Date	
Contractor	
Maintainer MEYER SEWER MPCA License f	No. 915 Telephone Number 651-457-016
What was done to the system?	Report Liquid Capacity in Gallons
Trank(s) Pumped	Tank 1: 750 X Pumped Tank 2: 750 X Pumpec
Sludge and scum measured. Do tanks need to be pumped?	Tank 3: Pumped Tank 4; Pumpec
Yes No (If no provide measurements below)	Total Gallons Pumped:
Visual Inspection (note any problems with the system):	NOTE: This does not serve as a compliance inspection
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank De	
y des descriptions.	= Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons/inch	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. X Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume = Total Slud	ge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
from	Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.