

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

		System Lo	cation	
Address 125	80 103 RC ST	(, n)		Telephone Number
City 5 11/1	water s	state MN Z	P55082Pro	perty ID No./GEO Code
Owner 5 cot	+ Potucile	umping Date	12/22/	15
		Contrac	tor	
Maintainer MEY	er sewer "	PCA License N	0. 915	Telephone Number 651-457-016
What was done to the system?			Report Liquid Capacity in Gallons	
Tank(s) Pumped Sludge and scum Do tanks need to Yes : No		(I)	Tank 3:	Pumped Tank 2: 1000 Pumped Pumped Tank 4: Pumped Ded: 2000
Visual inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection				
	*Tank Measureme	nts-Use Only I	f Tank(s) Were NOT	Pumped
Tank Length	in. X Tank Width In	. 🗶 Tank Dep	oth in. =	Tank Volume (cubic inches)
Tank Radius	in. X Tank Radius in.	X 3.14 =	Tank Volume (cub	oic inches)
Tank Volume (cu. in.)	/ 231.01 = Liquid	d Capacity	Gallons /	Tank Depth in. = Gallons/Inch
Sludge Level	in. X Gallons Per Inch	= Sludge Vol	ume Gallo	ns
Scum Level	in. X Gallons Per Inch = Scum Volume Gallons			
Sludge Volume	+ Scum Volume	= Total Sludg	ge and Scum Volume	Gallons
Total Sludge and Scu	m Volume / Liquid	Capacity	= Percent S	Sludge and Scum in Tank%
Scum Layer Effluent Sludge Layer		from	Depth measured invert of outlet to bottom of tank	Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.