

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location System Location	
Address 1544 Ramacky Acc 5	Telephone Number
City St Crack Beach State MAI 2	IP 66043 Property ID No./GEO Code
Owner Tom Mc Carthy Pumping Date	12/19/15
Contractor	
Maintainer MEYER SEWER MPCA License N	lo. 915 Telephone Number 651-457-016
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: /ar 200 Pumped Tank 2: Pumper
Sludge and scum measured. Do tanks need to be pumped?	Tank 3: Pumped Tank 4: Pumped
Yes No (If no provide measurements below)	Total Gallons Pumped: /200
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection	
*Tank Massuroment: Use Only (\$Tank/s) Way NOT Day	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width In. X Tank De	pth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. X Gallons Per Inch = Sludge Vo	lume Gallons
Scum Level in. X Gallons Per Inch = Scum Volu	ime Gallons
Sludge Volume + Scum Volume = Total Slud	ge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %	
from	Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.