

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location	
Address 8313 Quadrant	Ave S Telephone Number
City Hersting	State MM ZIP 5'5033 Property ID No./GEO Code
Owner Mante Brunbaugh	Pumping Date 5/19/15
Contractor	
Maintainer MEYER SEWER MPCA License No. 915 Telephone Number 651-459-016	
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped	Tank 1: / Day Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measureme	Total Gallons Pumped: /200
<u> </u>	<u>4-33</u>
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection.	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in. X Tank Depth in. = Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius	in. X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 :	= Liquid Capacity Gallons / Tank Depth in. = Gallons/Inch
Sludge Level in. X Gallons Per Inch	
Scum Level in. X Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	= Totąl Sludge and Scum Volume Gallons
Total Sludge and Scum Volume	/ Liquid Capacity = Percent Sludge and Scum in Tank %
	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than
Scum Layer	12 inches from the bottom of the outlet baffle; or
Effluent	from invert of outlet 2. Total sludge and scum volume is greate
Sludge Layer	pipe to bottom of tank than 25 percent of the tank's liquid capacity.
Siddyc Layer	
<u>Victorial de la constanta de </u>	
Signature Cal	Date 5/12/5 Reset Form