

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-673Q

SSTS MAINTENANCE REPORT

System Location			
Address 2795 Wel Les		Telephone Number	
City St. Www.ter	State M	1 ZIP 55083 Prope	rty ID No./GEO Code
Owner Mick kcs/hmitter Pumping Date 8/25/15			
Contractor			
Maintainer MEYER SE	EWER MPCA Licer	nse No. 915 T	elephone Number 651-459-016
What was done to the system?		Report	Liquid Capacity in Gallons
Tank(s) Pumped		Tank 1: 1300	Pumped Tank 2: Pumped
Sludge and scum measured.		Tank 3:	Pumped Tank 4: Pumped
Do tanks need to be pumped? Yes No (If no provide measurements below)		Total Gallons Pumpe	d: 1200
Tes To (in no provide mediane mento delony)			
RECEIVED			
JAN 0 5 2016			AN 05 2016
PUBLIC HEALTH			
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped			
Tank Length in. X T	ank Width in. X Tar	ik Depth in. = T	ank Volume (cubic inches)
Tank Radius in. X	ank Radius in. X 3.	14 = Tank Volume (cubic	inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch			
Sludge Level in. X G	allons Per Inch = Sludg	ge Volume Gallons	
Scum Level in. X Gallons Per Inch = Scum Volume Gallons			
Słudge Volume + So	cum Volume = Total	Sludge and Scum Volume	Gallons
Total Sludge and Scum Volume / Liquid Capacity = Percent Sludge and Scum in Tank %			
Scum Layer Effluent Sludge Layer		Tank Depth measured from invert of outlet pipe to bottom of tank	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greater than 25 percent of the tank's liquid capacity.