

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location					
Address 893	2 Militar	y Road)	Telephone Number	
City Wood	bury o	State MW	ZIP55/27 Pro	perty ID No./GEO Code	
Owner Mancy Wolterstor Permping Date 12/18/15					
Contractor					
Maintainer MEYE	RSEWER	MPCA License	No. 915	Telephone Number 651-457-016	
What was done to the system?			Report Liquid Capacity in Gallons		
Sludge and scum measured. Do tanks need to be pumped? Yes : No (If no provide measurements below)		ts below)	10-7	Pumped Tank 2: Pumped Pumped Tank 4: Pumped	
Visual inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection					
	*Tank Meası	irements-Use Only	If Tank(s) Were NOT	Pumped	
Tank Length	in. X Tank Width	in. X Tank Do	epth in. =	Tank Volume (cubic inches)	
Tank Radius	in. 🗶 Tank Radius	in. X 3.14	= Tank Volume (cub	ic inches)	
Tank Volume (cu. in.)	/ 231.01 =	Liquid Capacity	Gallons /	Tank Depth in. = Gallons/Inch	
Sludge Level	in. X Gallons Per Inch	= Sludge Vi	olume Gallor	าร	
Scum Level in. X Gallons Per Inch = Scum Volume Gallons					
Sludge Volume + Scum Volume = Total Sludge and Scum Volume Gallons					
Total Sludge and Scur	m Volume /	Liquid Capacity	= Percent S	sludge and Scum in Tank%	
Scum Layer Effluent Sludge Layer		fron	k Depth measured n invert of outlet e to bottom of tank	Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.	