

## DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

System Location	
Address 1965 Quinlan Aus	· S Telephone Number
City St. Croix Beach State MW ZIPS5047 Property ID No./GEO Code	
Owner Mona Capuzzi Pumping Date 10/7/15	
Contractor	
Maintainer MEYER SEWER MPC	A License No. 915 Telephone Number 651-459-016.
What was done to the system?	Report Liquid Capacity in Gallons
Tank(s) Pumped Z	Tank 1: 1000 Pumped Tank 2: 1000 Pumped
Sludge and scum measured.  Do tanks need to be pumped?	Tank 3: Pumped Tank 4: Pumped
Yes No (If no provide measurements below)	Total Gallons Pumped: 2000
Visual Inspection (note any problems with the syste	nm): NOTE: This does not serve as a compliance inspection.
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. <b>X</b> Tank Width in. <b>X</b> Tank Depth in. = Tank Volume (cubic inches)	
Tank Radius in. X Tank Radius in. X 3.14 = Tank Volume (cubic inches)	
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. X Gallons Per Inch =	Sludge Volume Gallons
Scum Level in. X Gallons Per Inch =	Scum Volume Gallons
Sludge Volume + Scum Volume =	Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid C	apacity = Percent Sludge and Scum in Tank %
Scum Layer  Effluent  Sludge Layer	*Tanks must be pumped if either of the following conditions exist:  1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or  2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.
Signature All	Date 10/7/15 Reset Form