

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location

Address 273 Quant for	Telephone Number
City Lakeland	State MN ZIP 55043 Property ID No./GEO Code
Owner Lynda Beinlich	Pumping Date 10/29/15
	Contractor
Maintainer MEYER SEWER	MPCA License No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
 Zank(s) Pumped □ Sludge and scum measured. □ Do tanks need to be pumped? □ Yes □ No (If no provide measurements be 	Tank 1: Pumped Tank 2: Pumped Tank 3: Pumped Tank 4: Pumped Total Gallons Pumped:
Visual Inspection (note any problems with the	NOTE: This does not serve as a compliance inspection RECEIVED JAN 07 2016 PUBLIC HEALTH
*Tank Measuren	nents-Use Only If Tank(s) Were NOT Pumped
Tank Length in. X Tank Width	in. X Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. χ Tank Radius	in. X 3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Lic	quid Capacity Gallons / Tank Depth in. = Gallons / Inch
Sludge Level in. X Gallons Per Inch	= Sludge Volume Gallons
Scum Level in. X Gallons Per Inch	= Scum Volume Gallons
Sludge Volume + Scum Volume	= Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liqu	uid Capacity = Percent Sludge and Scum in Tank %
Scum Layer Effluent Sludge Layer	*Tanks must be pumped if either of the following conditions exist: 1. The top of the sludge layer is less than 12 inches from the bottom of the outlet baffle; or 2. Total sludge and scum volume is greate than 25 percent of the tank's liquid capacity.