

DEPARTMENT OF PUBLIC MEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

		4	Syste	em Location				
Address //77	5	122 Nd st	5, S.		Telephone Number			
City Hastin	95		State	N ZIP55033	Property ID No./GEO Code			
Owner Ray	Bla	LU .	Pumping		15			
0			Co	ontractor				
Maintainer MEY	ER_	SEWER	MPCA Lice	ense No. 915	Telephone Number	51-459-016		
What was done to the system?					Report Liquid Capacity in Gallons			
Tank(s) Pumped 2				Tank 1: 1250 Pumped Tank 2: 1250 Pumper				
Sludge and scum measured.				Tank 3:	Pumped Tank 4;	Pumped		
Do tanks need to be pumped? Yes No (If no provide measurements below)					Pumped: 2500			
		any problems with ti			s does not serve as a con	npliance inspection		
					RECEIVI	1500 (5300) 1000 (5300)		
					JAN 0 7 701			
					. 3/411 9 1 2011	,		
			And the Property of the Control of t		- PUDLICATA	7 S S S S S S S S S S S S S S S S S S S		
-	····	*Yank Measu	rements-Use	Only If Tank(s) Were	NOT Pumped			
Tank Length	in.	X Tank Width	in. X Ta	nk Depth i	n. = Tank Volume (cubic ir	ches)		
Tank Radius	in.	χ Tank Radius	in. X 3	.14 = Tank Volum	e (cubic inches)			
Tank Volume (cu. in.)	/ 231.01 =	Liquid Capac	ity Gallo	ons / Tank Depth in. =	Gallons/Inch		
Sludge Level	in.	X Gallons Per Inch	= Slud	ge Volume	Gallons	•		
Scum Level	in.	X Gallons Per Inch	= Scur	n Volume	Gallons			
Sludge Volume		+ Scum Volume	= Tota	I Sludge and Scum Vo	olume Gallons			
Total Sludge and Sci	um Vo	lume /	Liquid Capacit	y = Per	cent Sludge and Scum in Ta	nk95		
	• ** • ** • *		[*Tanks must be pun following condition			
Scum Layer 1				1. The top of the sludge layer is less than 12 inches from the bottom of the outlet				
Effluent					ed baffle; or			
				from invert of outlet pipe to bottom of ta	than 25 percent of t	than 25 percent of the tank's liquid		
Sludge Layer					capacity. 	capacity.		