

DEPARTMENT OF PUBLIC HEALTH AND ENVIRONMENT

GOVERNMENT CENTER

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

SSTS MAINTENANCE REPORT

System Location System Location	
Address 8335 Q 4 R/	Telephone Number
	e MN ZIP 55/24 Property ID No./GEO Code
	pping Date 10/6/15
	Contractor
Maintainer MEYER SEWER MPC	A License No. 915 Telephone Number 651-459-016
What was done to the system?	Report Liquid Capacity in Gallons
A Tank(s) Pumped	Tank 1: /dce/ Pumped Tank 2: Pumped
Sludge and scum measured.	Tank 3: Pumped Tank 4: Pumped
Do tanks need to be pumped?	
Yes No (If no provide measurements below)	Total Gallons Pumped: /200
Visual Inspection (note any problems with the system): NOTE: This does not serve as a compliance inspection	
*Tank Measurements-Use Only If Tank(s) Were NOT Pumped	
Tank Length in. X Tank Width in.)	(Tank Depth in. = Tank Volume (cubic inches)
Tank Radius in. X Tank Radius in.)	(3.14 = Tank Volume (cubic inches)
Tank Volume (cu. in.) / 231.01 = Liquid Capacity Gallons / Tank Depth in. = Gallons / Inch	
Sludge Level in. X Gallons Per Inch = Sludge Volume Gallons	
Scum Level in. X Gallons Per Inch = Scum Volume Gallons	
Sludge Volume + Scum Volume =	Total Sludge and Scum Volume Gallons
Total Sludge and Scum Volume / Liquid Ca	pacity = Percent Sludge and Scum in Tank %
	*Tanks must be pumped if either of the
	following conditions exist: 1. The top of the sludge layer is less than
Scum Layer II	12 inches from the bottom of the outlet
Effluent	Tank Depth measured baffle; or 2. Total sludge and scum volume is greate.
	from invert of outlet pipe to bottom of tank than 25 percent of the tank's liquid
Sludge Layer	capacity.