

## OUYLINDERT CEITIEN

14949 62nd STREET NORTH P.O. BOX 6 STILLWATER, MN 55082-0006 Office: 651-430-6655 TDD: 651-430-6246 FAX: 651-430-6730

## SSTS MAINTENANCE REPORT

		Syste	m Location		
Address 737	Quentin	AUE. S	Ĵ	Telephone Number	
City Lalcelan		State Nu	J ZIP 55,043 Prop	perty ID No./GEO Code	
Owner John	RUDRECHT	Pumping [	- 1- 1		
		Co	ntractor		
Maintainer MEYE	RSEWER	MPCA Lice	nse No. 915	Telephone Number 651-4	59-016
What was done to the system?			Report Liquid Capacity in Gallons		
Tank(s) Pumped	7_		Tank 1: 1000	Pumped Tank 2: / (2002)	Pumped
Sludge and scum measured.  Do tanks need to be pumped?			Tank 3:	Pumped Tank 4:	Pumped
Yes No (If no provide measurements below)			Total Gallons Pump	ed: 2000	
Visual Inspection (r	note any problems with th	ne system):	NOTE: This doe	es not serve as a compliance	inspection.
		7			
	e				
				·	
	*Tank Measu	rements-Use	Only If Tank(s) Were NOT	Pumped	
Tank Length	in. <b>X</b> Tank Width	in. <b>X</b> Tai	nk Depth in. =	Tank Volume (cubic inches)	
Tank Radius	in. <b>X</b> Tank Radius	in. <b>X 3.</b>	. <b>14</b> = Tank Volume (cub	oic inches)	
Tank Volume (cu. in.)	/ 231.01 =	 Liquid Capaci	ty Gallons /	Tank Depth in. = Gallons/	/Inch
Sludge Level	in. <b>X</b> Gallons Per Inch	= Slude	ge Volume Gallo	ns	
Scum Level	in. <b>X</b> Gallons Per Inch	= Scun	n Volume Gallo	ns	
Sludge Volume	+ Scum Volume	= Tota	I Sludge and Scum Volume	e Gallons	
Total Sludge and Scu	m Volume /	 Liquid Capacit	y = Percent	Sludge and Scum in Tank	%
Scum Layer Effluent Sludge Layer			Tank Depth measured from invert of outlet pipe to bottom of tank	*Tanks must be pumped if eifollowing conditions exist:  1. The top of the sludge laye  12 inches from the bottom of baffle; or  2. Total sludge and scum voluthan 25 percent of the tank's capacity.	r is less than of the outlet ume is greate
Signature ///	7/1		Date 9/5/5	Reset Fo	rm
" We	<del>(</del>	<del></del>	10/1-		